

WEPBF 15-150 Quick (613085420) 6" Flat-Head Angle Grinder Cardboard box

Order no. 613085420 EAN 4007430275745



Representative picture





















- Powerful flat-head angle grinder for working quickly in particularly acute angles down to 39° with the highest user protection
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT) side handle for vibration damping to protect the user's health
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Fastest brake system for the highest user protection: patented, mechanical disc brake stops the disc after switching off within 2 seconds, even in the event of a power cut
- Electronic safety shutdown of the motor reduces kickback if the disc stops unexpectedly- for high user protection
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical values	
Parameters	
Amps	13.5 AMPS
Minimum accessible angle	39 °
Disc diameter	6"
Rated input power	1550 W
Output power	900 W
No-load speed	9600 RPM
Speed at rated load	9600 RPM
Torque	35 in-lbs
Spindle thread	5/8" - 11 UNC
Weight (without power cable)	6.4 lbs
Cable length	8 ft
Grip circumference	7 3/4 "
Vibration	
Surface grinding	6.8 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Grinding with sandpaper	3.4 m/s²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	89 dB(A)
Sound power level (LwA)	100 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard

Inner support flange

Quick adjusting nut

Side handle Metabo VibraTech (MVT)

1 Lamellar grinding disc Flexiamant Super Convex (150mm; P60)

www.metabo.com 2/2