

SB 18 LTX-3 BL I Metal (603183850) Cordless hammer drill 18V; Cardboard box

Order no. 603183850 EAN 4061792212107



Product may differ from Image











- - The metal expert: brushless 3-speed cordless hammer drill with maximum power and automatically re-tightening chuck
 - Extremely powerful chuck with re-tensioning function against slipping of the bit and high degree of concentricity
 - Third speed setting with high torque (max. 4,000/min) for extended range of application and even faster drilling progress, especially in metal
 - Hammer drill function for drilling in masonry
 - Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
 - Precision Stop: electronic torque control with increased precision for precise, delicate working
 - Overload protection: protects the motor from overheating
 - Electronic safety shutdown: no kickback if the drill bit stops unexpectedly for high user safety
 - Integrated LED work light with afterglow function for optimal brightness in the work area
 - With handy belt hook and bit case which can be fixed either on the right or left side
 - Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

www.metabo.com 1/2



Technical data		
Characteristics		
Battery voltage	18 V	
Maximum torque, soft	65 Nm / 575.3 in-lbs	
Maximum torque, hard	130 Nm / 1150.6 in-lbs	
Adjustable torque	1 - 18 Nm // 8.9 - 159.3 in-lbs	
Drill-Ø masonry	16 mm / 5/8 "	
Drill Ø steel	16 mm / 5/8 "	
Drill-Ø soft wood	68 mm / 2.68 "	
No-load speed	0 - 450 / 0 - 2000 / 0 - 4000 rpm	
Maximum impact rate	38000 bpm	
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "	
Collar diameter	43 mm / 1.69 "	
Weight without battery pack	2 kg / 4.4 lbs	
Weight with battery pack	3 kg / 6.6 lbs	
Vibration		
Drilling in metal	3 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Impact drilling concrete	25 m/s ²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	98 dB(A)	
Sound power level (LwA)	109 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Futuro Top keyless chuck

Side handle

C-wrench

without battery pack, without charger

www.metabo.com 2/2