

WE 15-125 Quick (600448190) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600448190 EAN 4007430245502



Product may differ from Image















- Highest service life for extreme applications: robust, powerful angle grinder with maximum power density in its class for quick work progress
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data		
Characteristics		
Disc-Ø	125 mm // 5 "	
Rated input power	1550 W	
Output power	940 W	
No-load speed	11000 rpm	
Speed at rated load	11000 rpm	
Torque	3.5 Nm / 31 in-lbs	
Spindle thread	M 14	
Handle circumference	206 mm / 8 1/8 "	
Weight (without power cable)	2.5 kg / 5.5 lbs	
Cable length	4 m / 13 ft	
Vibration		
Surface grinding	6 m/s ²	
Uncertainty of measurement K	1.5 m/s ²	
Grinding with sandpaper	3.6 m/s ²	
Uncertainty of measurement K	1.5 m/s ²	
Noise emission		
Sound pressure level	93 dB(A)	
Sound power level (LwA)	104 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Metabo VibraTech (MVT) side handle

www.metabo.com 2/2