

## KFM 18 LTX 3 RF (601754840) Cordless bevelling tool for metal 18V; metaBOX 215

Order no. 601754840 EAN 4007430291462



RESTANT RODUCTION

- The most powerful cordless metal bevelling tool for 45° chamfers up to 4 mm and radii of 2 and 3 mm
- Surfaces free from oxide and burrs as ideal preparation for the application of powder or paint coatings for maximum protection from corrosion
- One-touch controller: Patented, tool-free setting of the cutting depth in 0.1 steps; stop points for short setting times, and protection against unintentional adjustment of the cutting depth when working
- Slim milling head and ball bearing stationary seal ring for working in pipes and on curves
- Guide stop for a uniform finish and high quality of the surface when processing straight sheets
- Bail handle adjusts without tools for secure, even guiding
- Battery pack can be rotated in 90° steps for best ergonomics in any working position
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- Detachable dust protection filter protects motor from coarse particles
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Product may differ from Image

## Technical data

## Characteristics

Type of battery pack	LiPOWER
Battery voltage	18 V
No-load speed	7000 rpm
Type of edges	Chamfer and radius
Max. chamfer width 45°	6 mm / 1/4 "
Max. chamfer height at 45°	4 mm / 5/32 "
Possible radii	R2 / R3
Grading of cutting depth setting	0.1 mm / 0.00394 "
Curves smallest internal Ø	13 mm
Weight without battery pack	2.4 kg / 5.3 lbs
Weight with battery pack	3.1 kg / 6.8 lbs
Vibration	
Vibration	0.94 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Noise emission	
Sound pressure level	84 dB(A)
Sound power level (LwA)	95 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

2 Carbide indexable inserts 45° chamfer 2 Carbide indexable inserts radius R2 2 Carbide indexable inserts radius R3 Guide Stop Screwdriver for Torx screws 15 Bow-type handle Dust Protection Filter metaBOX 215 without battery pack, without charger