

## WEV 11-125 Quick (603625000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box; with speed control, quick-locking nut

Order no. 603625000 EAN 4061792176409



Product may differ from Image













- Low fatigue as never before: compact angle grinder with adjustable speed and smallest handle circumference in its class for perfect ergonomics
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Thumbwheel controlled Vario-Constamatic (VC)-Full wave electronics ideal for working on materials requiring customised speeds, and at speeds which remain almost constant under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data	
Characteristics	
Disc-Ø	125 mm // 5 "
Rated input power	1100 W
Output power	640 W
No-load speed	2800 - 10500 rpm
Speed at rated load	8800 rpm
Torque	3 Nm / 26.6 in-lbs
Spindle thread	M 14
Handle circumference	193 mm / 7.5594 "
Weight (without power cable)	2.1 kg / 4.6 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s²
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Side handle

www.metabo.com 2/2