

WEF 9-125 Quick (613060190) Flat-head angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 613060190
EAN 4007430243676



Product may differ from image



- Most compact flat-head angle grinder for working at acute angles down to 43°
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Metabo Marathon motor with patented dust protection for long service life
- Constamatic (C)-Full wave electronics: fast work progress by means of almost constant speed under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Electronic overload protection, soft start and restart protection
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

| | |
|------------------------------|------------------|
| Minimum accessible angle | 43 ° |
| Disc-Ø | 125 mm / 5 " |
| Rated input power | 910 W |
| Output power | 430 W |
| No-load speed | 10000 rpm |
| Speed at rated load | 8200 rpm |
| Torque | 2 Nm / 18 in-lbs |
| Spindle thread | M 14 |
| Weight (without power cable) | 2.1 kg / 4.6 lbs |
| Cable length | 4 m / 13 ft |
| Handle circumference | 197 mm / 7 3/4 " |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 5.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 88 dB(A) |
| Sound power level (LwA) | 99 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- Guard
- Inner support flange
- Quick-locking nut
- Side handle
- 1 Flap disc Flexiamant Super Convex (125mm; P60)