# DH 330 (0200033019) Bench Thicknesser

**(220-240 V / 50 Hz); Cardboard box**

Order no. 0200033019
EAN 4003665424484




Product may differ from Image

- Ideal for mobile use due to low weight
- Stable gear for uniform work piece feed
- Convenient height adjustment with crank handle
- Easy setting of common passage heights using stop points
- Powerful universal motor for powerful lugging drive and even planing result
- Restart protection: prevents unintentional start-up after power supply interruption
- Precise thickness adjustment for quick and exact planing
- Large feed and exit tables support the conveyance of long materials
- Planing locking mechanism prevents unintentional adjustment of the chip removal setting

## Technical data

### Characteristics

| | |
|---|---|
| Dimensions | 579 x 857 x 574 mm // 1.9 x 2.9 x 1.9 ft |
| Chip removal bench thicknesser | 0 - 3 mm // 0 - 1/8 " |
| Material thickness table | Cast aluminium / special steel aluminium |
| Thickness table L x W | 840 x 330 mm // 33 x 13 " |
| Passage height/width | 152 / 330 mm // 6 / 13 " |
| Feed rate | 7.51 m/min / 25 ft/min |
| Diameter of blade shaft | 47 mm / 1 7/8 " |
| Number of blades | 2 |
| Revolutions of blade shaft | 9800 rpm |
| Mains voltage | 220 - 240 V |
| Rated input power | 1800 W |
| Weight | 35 kg / 77.2 lbs |

### Noise emission

| | |
|---|---|
| Uncertainty of measurement K | 4 dB(A) |

## Scope of delivery

2 integrated HSS reversible planer blades

Push stick

Extraction Nozzles