

TE 24-230 MVT CED (600434500) Diamond cutting system (220-240 V / 50 - 60 Hz); Plastic Carry Case; with diamond cutting disc UP

Order no. 600434500 EAN 4061792122291



Product may differ from Image











- Powerful diamond cutter for low-dust dry cuts up to 60 mm in mineral materials
- Best view on the cutting line thanks to the open design of the dust extraction shroud
- Efficient dust extraction for health protection and clean construction sites
- Fast work progress and long service life thanks to powerful Metabo Marathon-motor
- Ideal for precise, horizontal cutting thanks to pushing cut; conversion to pulling cut possible
- Precise cuts on even surfaces thanks to metal base plate with rollers
- Safety and control in any situation: Soft start, Metabo VibraTech (MVT) vibration damping, electronic safety shutdown and restart protection
- Robust die-cast aluminium dust extraction shroud with tool-free setting of the cutting depth
- Auto-stop carbon brushes to protect the motor
- Connection for dust extraction Ø 35/41 mm

www.metabo.com 1/2



| Technical data | |
|------------------------------|----------------------|
| Characteristics | |
| Cutting disc Ø | 230 mm / 9 " |
| Max. cutting depth | 60 mm / 2 3/8 " |
| Rated input power | 2400 W |
| Output power | 1600 W |
| No-load speed | 6600 rpm |
| Spindle thread | M 14 |
| Weight (without power cable) | 8.1 kg / 17.9 lbs |
| Cable length | 4 m / 13 ft |
| Vibration | |
| Vibration | 4.1 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 99 dB(A) |
| Sound power level (LwA) | 110 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Extraction hood CED 230

Diamond cutting disc UP

Flat-pin spanners

Inner support flange

Spacer Rings

Nut with two holes

Side handle

Plastic carry case

www.metabo.com 2/2