

## WEA 17-125 Quick (600534190) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600534190 EAN 4007430246080



Product may differ from Image

















- Maximum productivity: 1,700 Watt angle grinder with the power of a large grinder and the compactness of a small one for quickest material removal on industrial applications
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Best anti-vibration system: integrated auto-balancer for up to 50% less hand-arm vibrations, longer service life of the machine and up to twice the service life of the grinding wheels
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



| Technical data               |                      |
|------------------------------|----------------------|
| Characteristics              |                      |
| Disc-Ø                       | 125 mm // 5 "        |
| Rated input power            | 1700 W               |
| Output power                 | 1040 W               |
| No-load speed                | 11000 rpm            |
| Speed at rated load          | 11000 rpm            |
| Torque                       | 3.7 Nm / 33 in-lbs   |
| Spindle thread               | M 14                 |
| Handle circumference         | 206 mm / 8 1/8 "     |
| Weight (without power cable) | 2.5 kg / 5.5 lbs     |
| Cable length                 | 4 m / 13 ft          |
| Vibration                    |                      |
| Surface grinding             | 4 m/s²               |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 3 m/s²               |
| Uncertainty of measurement K | 1.5 m/s²             |
| Noise emission               |                      |
| Sound pressure level         | 93 dB(A)             |
| Sound power level (LwA)      | 104 dB(A)            |
| Uncertainty of measurement K | 3 dB(A)              |

## Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Metabo VibraTech (MVT) side handle

www.metabo.com 2/2