

## SSW 18 LTX 300 BL (602395890) Cordless impact wrench 18V; Cardboard box

Order no. 602395890  
EAN 4007430331892



Product may differ from Image



- Compact cordless impact driver with 1/2" male square and 300 Nm, versatile application
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Automatic Power Shift (APS) supports working with self-tapping screws: automatic torque reduction after drilling to prevent overtightening.
- Low kick-back operation with extremely high torque
- Twelve speed/torque levels for a wide range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Technical data****Characteristics**

|                             |                             |
|-----------------------------|-----------------------------|
| Battery voltage             | 18 V                        |
| Max. screw size             | M18                         |
| Max. no-load speed          | 0 - 2650 rpm                |
| Maximum impact rate         | 3750 bpm                    |
| Maximum torque              | 300 Nm / 220 ft. lbs        |
| Max. loosening torque       | 480 Nm / 355 ft. lbs        |
| Speed/torque levels         | 12                          |
| Bit retainer                | Male square 1/2" (12.70 mm) |
| Weight without battery pack | 1.1 kg / 2.4 lbs            |
| Weight with battery pack    | 1.7 kg / 3.7 lbs            |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Impact screwdriving          | 7 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

**Noise emission**

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 95 dB(A)  |
| Sound power level (LwA)      | 106 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

**Scope of delivery**

Belt Hook  
without battery pack, without charger