

## HS 8745 (608745000) Hedge trimmer (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 608745000 EAN 4007430180759



Product may differ from Image





- Patented Metabo handle system with additional switch for up to 50% more reach and range
- · Low weight avoids fatigue when working
- Patented mechanical quick blade stop (in 0.05 seconds) for improved safety
- Blades with special geometry generate less wear and thus deliver 200% longer service life
- Clean cut thanks to diamond-ground blade teeth on both sides at a30° angle
- Lower safety blade for high safety at work
- Metabo S-automatic safety clutch: Protects blades and gears when debris or large branches stop the blades
- Fatigue-proof operation due to ergonomic full grip bow-type handle design and optimum centre of gravity position
- Very quiet running due to shear blades running in opposite direction
- User-friendly guidance of machine exhaust in all working situations
- Easy servicing thanks to cable replacement cover
- Cable strain relief prevents the unintentional disconnection of the plug-in connection
- Trigger guard with twig feed protects user and gear from kickbacks

www.metabo.com 1/2



Technical data	
Characteristics	
Max. cutting thickness	20 mm / 3/4 "
Cutting length	45 cm / 18 "
Blade clearance	34 mm / 1 3/8 "
Number of strokes (No Load)	3100 spm
Rated input power	560 W
Weight (without power cable)	3.8 kg / 8.4 lbs
Cable length	0.3 m / 1 ft
Vibration	
Idle	3.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	84 dB(A)
Sound power level (LwA)	95 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Trigger guard

Container

www.metabo.com 2/2