

## WEF 15-125 Quick (613082000) Flat-head angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 613082000  
EAN 4007430275707



Product may differ from Image



- Powerful flat-head angle grinder for working quickly in acute angles down to 43°
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT) side handle for vibration damping to protect the user's health
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

### Characteristics

Minimum accessible angle	43 °
Disc-Ø	125 mm / 5 "
Rated input power	1550 W
Output power	940 W
No-load speed	11000 rpm
Speed at rated load	11000 rpm
Torque	3.5 Nm / 31 in-lbs
Spindle thread	M 14
Weight (without power cable)	2.7 kg / 5.9 lbs
Cable length	4 m / 13 ft
Handle circumference	206 mm / 8 1/8 "

### Vibration

Surface grinding	6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	3.6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	91 dB(A)
Sound power level (LwA)	102 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard  
 Inner support flange  
 Quick-locking nut  
 Metabo VibraTech (MVT) side handle  
 1 Flap disc Flexiamant Super Convex (125mm; P60)