

## SXE 150-2.5 BL (615025700) Random orbital sander (220-240 V / 50 - 60 Hz); metaBOX 145

Order no. 615025700  
EAN 4007430320834



Product may differ from Image



- Extremely light and flat random orbital sander with symmetrical design for easy change of hands or operation with two hands
- Orbit diameter 2.5 mm for highest surface quality with good material removal
- Non-slip paddle switch with dead man function for safe starting and optionally also control of the speed
- Vario Tacho Constamatic (VTC) Full-wave Electronics for grinding with materials requiring customised speeds, which remain constant under load
- Electronic presetting of the desired speed range
- Soft start minimises surface damage when placing the machine on the work surface
- Unique Metabo brushless motor highest efficiency when grinding, also in continuous mode
- Low vibrations for convenient continuous mode
- Overload protection: protects the motor from overheating
- Separate main switch protects from unintentional start
- Motor and plate brake permits quick placing down of the machine after use
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Multi-hole sanding pad for effective extraction and a longer service life of the sanding medium
- When working with 125 mm sanding sheets, the sanding pad "multi-hole" Ø 125 mm can be used (accessory 630264000)
- Service-friendly with exchangeable cable
- With metaBOX, the intelligent solution for transport and storage

## Technical data

### Characteristics

|                                |                  |
|--------------------------------|------------------|
| Diameter of backing pad        | 150 mm / 5.91 "  |
| Rated input power              | 350 W            |
| No-load speed                  | 4000 - 10000 rpm |
| Orbital frequency with no load | 8000 - 20000 opm |
| Orbit diameter                 | 2.5 mm / 0.1 "   |
| Weight (without power cable)   | 1 kg / 2.2 lbs   |
| Cable length                   | 4.3 m / 14 ft    |

### Vibration

|                  |                      |
|------------------|----------------------|
| Surface grinding | 2.4 m/s <sup>2</sup> |
|------------------|----------------------|

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 71 dB(A) |
| Sound power level (LwA)      | 82 dB(A) |
| Uncertainty of measurement K | 2 dB(A)  |

## Scope of delivery

Sanding pad "multi-hole" with hook and loop  
 Open-jawed spanner  
 metaBOX 145