

WEV 15-150 HT (600563420) Angle grinder (110-120 V / 60 Hz); Cardboard box; with speed control

Order no. 600563420 EAN 4007430320353



Product may differ from Image











- · Optimum processing of stone: robust, powerful angle grinder with gear reduction and reduced, adjustable speed for material-friendly working
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data	
Characteristics	
Disc-Ø	150 mm // 6 "
Rated input power	1550 W
Output power	900 W
No-load speed	2000 - 7600 rpm
Speed at rated load	7600 rpm
Torque	5 Nm / 44 in-lbs
Spindle thread	5/8" - 11 UNC
Handle circumference	206 mm / 8 1/8 "
Weight (without power cable)	2.6 kg / 5.7 lbs
Cable length	2.5 m / 8 ft
Vibration	
Surface grinding	4.7 m/s²
Uncertainty of measurement K	1.5 m/s ²
Polishing	2.5 m/s²
Uncertainty of measurement K	1.5 m/s ²
Grinding with sandpaper	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard

Side handle

Flat-pin spanners

Inner support flange

Nut with two holes

www.metabo.com 2 / 2