

## WEPBA 17-150 Quick RT DS (600606420) Angle grinder (110-120 V / 60 Hz); Cardboard box

Order no. 600606420  
EAN 4007430320261



Product may differ from Image



- Maximum productivity thanks to top performance with low weight
- Steel ring to accommodate the carabiner secures the angle grinder from falling down when working at great heights
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Metabo Longlife-motor with new cooling and carbon brush system for twice the service life
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Reduced vibrations for low-fatigue working thanks to Metabo VibraTech (MVT) side handle and integrated Auto-balancer
- Highest degree of user safety thanks to patented, mechanical disc brake and deadman's switch: disc stop in 2 seconds after releasing even in case of a power cut
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

### Characteristics

|                              |                    |
|------------------------------|--------------------|
| Disc-Ø                       | 150 mm // 6 "      |
| Output power                 | 1000 W             |
| No-load speed                | 9600 rpm           |
| Speed at rated load          | 9600 rpm           |
| Torque                       | 4.4 Nm / 39 in-lbs |
| Spindle thread               | 5/8" - 11 UNC      |
| Handle circumference         | 138 mm / 5.438 "   |
| Weight (without power cable) | 2.8 kg / 6 lbs     |
| Cable length                 | 2.5 m / 8 ft       |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 6 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 4.9 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 92 dB(A)  |
| Sound power level (LwA)      | 103 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Guard  
Metabo VibraTech (MVT) side handle  
Inner support flange  
M-Quick flange nut