

WEBA 20-125 Quick BL (600642190) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600642190 EAN 4061792207219



Product may differ from Image



















- Compact 2000 Watt angle grinder for industrial use: with Brushless motor for maximum productivity and unrivalled service
- Highly efficient, service-free Marathon Brushless motor: patented cooling and innovative dust protection for triple service life compared to brush motors
- Tacho Constamatic (TC) Electronics: extremely fast work progress thanks to high speed even under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Best anti-vibration system: integrated auto-balancer for up to 50% less hand-arm vibrations, longer service life of the machine and up to twice the service life of the grinding wheels
- Best ratio of performance to handle circumference on the market for low-fatigue working
- Highest level of user safety thanks to fast brake, anti-kickback, overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Particularly easy servicing thanks to cable replacement cover
- Detachable dust filter protects motor from coarse particles

www.metabo.com 1/2



| Technical data | | |
|------------------------------|------------------|--|
| Characteristics | | |
| Disc-Ø | 125 mm // 5 " | |
| Rated input power | 2000 W | |
| Output power | 1600 W | |
| No-load speed | 11000 rpm | |
| Torque | 3.5 | |
| Spindle thread | M 14 | |
| Weight (without power cable) | 2.6 kg / 5.7 lbs | |
| Cable length | 4 m / 13 ft | |
| Vibration | | |
| Surface grinding | 4.69 m/s² | |
| Uncertainty of measurement K | 1.5 m/s² | |
| Polishing | 2.18 m/s² | |
| Uncertainty of measurement K | 1.5 m/s² | |
| Uncertainty of measurement K | 1.5 m/s² | |
| Noise emission | | |
| Sound pressure level | 86 dB(A) | |
| Sound power level (LwA) | 97 dB(A) | |
| Uncertainty of measurement K | 3 dB(A) | |

Scope of delivery

Guard

M-Quick flange nut

Metabo VibraTech (MVT) side handle

Dust protection filter

Clip for cut-off guard

Inner support flange

www.metabo.com 2 / 2