

## KHE 2660 Quick (600663510) Combination hammer (220-240 V / 50 - 60 Hz); metaBOX 145 L

Order no. 600663510  
EAN 4007430309624



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for many different applications
- Perfect ergonomics thanks to the centre of gravity being near the hand and optimised handle contour
- Bottom switch protected against damage and dust
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo Marathon-motor with dust protection for long service life
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation
- Cable-protecting ball joint for optimal freedom of motion when working
- With metaBOX, the intelligent solution for transport and storage

## Technical data

### Characteristics

|                                     |                   |
|-------------------------------------|-------------------|
| Max. single blow energy (EPTA)      | 3 J               |
| Maximum impact rate                 | 4300 bpm          |
| Rated input power                   | 850 W             |
| Drill-Ø concrete with hammer drills | 26 mm / 1 1/32 "  |
| Drill-Ø masonry with core bits      | 68 mm / 2 11/16 " |
| Drill Ø steel                       | 13 mm / 1/2 "     |
| Drill-Ø soft wood                   | 32 mm / 1 1/4 "   |
| No-load speed                       | 0 - 1100 rpm      |
| Speed at rated load                 | 830 rpm           |
| Bit retainer                        | SDS-plus          |
| Collar diameter                     | 50 mm / 1 31/32 " |
| Weight (without power cable)        | 3.1 kg / 6.9 lbs  |
| Cable length                        | 4 m / 13 ft       |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Hammer drilling concrete     | 12.9 m/s <sup>2</sup> |
| Uncertainty of measurement K | 2.4 m/s <sup>2</sup>  |
| Chiseling                    | 8.5 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 89 dB(A) |
| Sound power level (LwA)      | 99 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end  
metaBOX 145 L  
rubber-coated side handle  
Drilling depth guide