

## UHE 2660-2 Quick Set (600697860) Multi hammer (220-240 V / 50 - 60 Hz); metaBOX 145 L; with SDS-plus drill bit/chisel set (10 pieces)

Order no. 600697860 EAN 4007430309617



Product may differ from Image











- Multi hammer with 4 functions: hammer drilling, drilling without impact in two speeds and chiselling
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for drilling in wood and metal
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Thumbwheel for preselection of the speed and impact rate
- Two-speed gear unit: two drilling speeds for effective drilling in wood and metal
- Metabo Marathon-motor with dust protection for long service life
- · High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Perfect ergonomics thanks to the centre of gravity being near the hand and optimised handle contour
- Bottom switch protected against damage and dust
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation
- Cable-protecting ball joint for optimal freedom of motion when working
- With metaBOX, the intelligent solution for transport and storage

www.metabo.com 1/2



Technical data	
Characteristics	
Max. single blow energy (EPTA)	2.8 J
Maximum impact rate	4200 bpm
Rated input power	800 W
Drill-Ø concrete with hammer drills	26 mm / 1 1/32 "
Drill-Ø masonry with core bits	68 mm / 2 11/16 "
Drill Ø steel	13 / 6 mm // 1/2 / 1/4 "
Drill-Ø soft wood	32 / 28 mm // 1 1/4 / 1 3/32 "
No-load speed	0 - 1050 / 0 - 2500 rpm
Speed at rated load	790 / 1860 rpm
Bit retainer	SDS-plus
Collar diameter	50 mm / 1 31/32 "
Weight (without power cable)	3.1 kg / 6.9 lbs
Cable length	4 m / 13 ft
Vibration	
Drilling in metal	3.3 m/s²
Uncertainty of measurement K	1.5 m/s²
Hammer drilling concrete	12.9 m/s <sup>2</sup>
Uncertainty of measurement K	2.4 m/s²
Chiseling	8.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	88 dB(A)
Sound power level (LwA)	99 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end Drilling depth guide metaBOX 145 L SDS-plus drill bit / chisel set (10 pieces) Keyless chuck for tools with cylindrical shank

rubber-coated side handle

www.metabo.com 2/2