

## **HWW 9000/100 G (600977000) Domestic waterwork (220-240 V / 50 Hz); Cardboard box**

Order no. 600977000

EAN 4007430239280



Product may differ from Image



- For automatic water supply, for garden irrigation and groundwater pumping as well as pumping, pumping empty, circulation of clear water
- Pressure vessel for energy-saving and low-noise provision of water
- Pressure switch at the tank for automatic activation in case of increased water demand
- Maintenance-free capacitor motor
- Overload protection: protects the motor from overheating
- High-quality slip seal system for long service life
- For garden irrigation with 1 to 6 sprinklers
- For single phase alternating current

**Technical data****Characteristics**

|                              |                                                  |
|------------------------------|--------------------------------------------------|
| Rated input power            | 1900 W                                           |
| Maximum delivery rate        | 9000 l/h / 2378 gal/h                            |
| Maximum delivery height      | 51 m / 167 ft                                    |
| Maximum pressure             | 5.1 bar / 74 psi                                 |
| Maximum suction height       | 9 m / 30 ft                                      |
| Switch-on pressure approx.   | 1.5 bar / 21.8 psi                               |
| Switch-off pressure approx.  | 3.9 bar / 56.6 psi                               |
| Suction port                 | 1 1/4" female thread                             |
| Discharge port               | 1" female thread                                 |
| Tank capacity, approximately | 100 l / 26.4 gal                                 |
| Pump housing                 | Grey cast iron                                   |
| Protection type IP           | IP X4                                            |
| Drive shaft                  | Stainless steel                                  |
| Tank                         | Steel                                            |
| Number of impellers          | 1                                                |
| Dimensions                   | 730 x 448 x 740 mm // 28 3/4 x 17 5/8 x 29 1/8 " |
| Weight                       | 39.9 kg / 83.6 lbs                               |
| Cable length                 | 1.5 m / 5 ft                                     |

**Noise emission**

|                              |            |
|------------------------------|------------|
| Sound pressure level         | 73 dB(A)   |
| Sound power level (LwA)      | 85.4 dB(A) |
| Uncertainty of measurement K | 3 dB(A)    |

**Scope of delivery**

Check Valve  
Fabric Sealing Tape