

HWA 3500 Inox (600978000) Automatic domestic water system (220-240 V / 50 Hz); Cardboard box

Order no. 600978000
EAN 4007430240514



Product may differ from Image



- For automatic water supply, for garden irrigation and groundwater pumping as well as pumping, pumping empty, circulation of clear water
- Intelligent electronics for automatic appropriate and energy-saving modes
- Metabo pump protection: automatic dry-run protection with LED display to protect the pump and high user safety
- Maintenance-free capacitor motor
- Overload protection: protects the motor from overheating
- High-quality slip seal system for long service life
- Durable stainless steel pump housing
- Separate water filling opening for comfortable operation of the pump
- Water drain plug (removable without tools) for protection in case of frost
- Rubberised feet for low-noise and low-vibration operation
- For garden irrigation with 1 or 2 sprinklers

Technical data

Characteristics

| | |
|-----------------------------|--|
| Rated input power | 1100 W |
| Maximum delivery rate | 3500 l/h / 925 gal/h |
| Maximum delivery height | 45 m / 148 ft |
| Maximum pressure | 4.5 bar / 65.3 psi |
| Maximum suction height | 8 m / 26 ft |
| Switch-on pressure approx. | 1.6 bar / 23.2 psi |
| Switch-off pressure approx. | 4.5 bar / 65.3 psi |
| Suction port | 1" female thread |
| Discharge port | 1" female thread |
| Pump housing | Stainless steel |
| Protection type IP | IP X4 |
| Drive shaft | Stainless steel |
| Number of impellers | 1 |
| Dimensions | 408 x 222 x 303 mm // 16 1/16 x 8 3/4 x 11 15/16 " |
| Weight | 10.6 kg / 23.4 lbs |
| Cable length | 1.5 m / 5 ft |

Noise emission

| | |
|------------------------------|------------|
| Sound pressure level | 65 dB(A) |
| Sound power level (LwA) | 77.8 dB(A) |
| Uncertainty of measurement K | 2.5 dB(A) |

Scope of delivery

Check Valve
Fabric Sealing Tape