

## HHW 4000/25 Inox (600982000) Domestic waterwork Cardboard box

Order no. 600982000  
EAN 4061792001558



Product may differ from Image



- For automatic water supply, for garden irrigation and groundwater pumping as well as pumping, pumping empty, circulation of clear water
- Pressure vessel for energy-saving and low-noise provision of water
- Pressure switch at the pump head for automatic activation in case of increased water demand
- Maintenance-free capacitor motor
- Overload protection: protects the motor from overheating
- High-quality slip seal system for long service life
- Durable stainless steel pump housing
- Separate water filling opening for simple operation of the pump
- Water drain plug (removable without tools) for protection in case of frost
- For garden irrigation with 1 to 3 sprinklers
- For single phase alternating current

## Technical data

### Characteristics

|                              |                                                   |
|------------------------------|---------------------------------------------------|
| Rated input power            | 1100 W                                            |
| Maximum delivery rate        | 4000 l/h / 1060 gal/h                             |
| Maximum delivery height      | 45 m / 147 ft                                     |
| Maximum pressure             | 4.5 bar / 65 psi                                  |
| Maximum suction height       | 8 m / 26 ft                                       |
| Switch-on pressure approx.   | 1.4 bar / 20.3 psi                                |
| Switch-off pressure approx.  | 3.2 bar / 46.4 psi                                |
| Suction port                 | 1" female thread                                  |
| Discharge port               | 1" female thread                                  |
| Tank capacity, approximately | 24 l / 6.3 gal                                    |
| Pump housing                 | Stainless steel                                   |
| Protection type IP           | IP X4                                             |
| Drive shaft                  | Stainless steel                                   |
| Tank                         | Steel                                             |
| Number of impellers          | 1                                                 |
| Dimensions                   | 470 x 270 x 590 mm // 18 1/2 x 10 5/8 x 23 7/32 " |
| Weight                       | 15.5 kg / 34.2 lbs                                |
| Cable length                 | 1.5 m / 5 ft                                      |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 68 dB(A)  |
| Sound power level (LwA)      | 81 dB(A)  |
| Uncertainty of measurement K | 2.9 dB(A) |

## Scope of delivery

Check Valve  
Fabric Sealing Tape