

## ST 18 L 90 (601047850) Cordless jigsaw 18V; Cardboard box

Order no. 601047850  
EAN 4061792256170



Product may differ from Image



- The daily helper for universal sawing applications: compact cordless jigsaw for cuts in wood up to 90 mm
- Metabo "Quick" for changing saw blades without tools and with automatic ejection
- Efficient chip blowing function for clear view of the cutting line
- Integrated LED work light for illumination of the cutting line
- Restart protection: prevents unintentional start-up after battery pack change
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                  |
|-----------------------------|------------------|
| Type of battery pack        | LiPOWER / LiHD   |
| Battery voltage             | 18 V             |
| Cutting depth wood          | 90 mm / 3 9/16 " |
| Cutting depth NF metal      | 25 mm / 1 "      |
| Cutting depth sheet steel   | 10 mm / 3/8 "    |
| Swivel range from / to:     | - 45 / + 45 °    |
| Pendulum stroke levels      | 4                |
| Strokes in idle             | 750 - 3000 rpm   |
| Saw blade stroke            | 22 mm / 7/8 "    |
| Weight without battery pack | 1.5              |
| Weight with battery pack    | 1.9              |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Sawing wood                  | 7.6 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Sawing metal                 | 8.7 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 95 dB(A) |
| Sound power level (LwA)      | 87 dB(A) |
| Uncertainty of measurement K | 5 dB(A)  |

## Scope of delivery

Extraction nozzle  
 2 Jigsaw blades  
 Hexagonal wrench  
 without battery pack, without charger  
 Protective glass  
 Chip guard plate