

GP 400 (601053420) Die grinder
(110-120 V / AC/DC 0/50/60 Hz); Cardboard box

Order no. 601053420
EAN 4061792257610



Product may differ from Image



- Robust die grinder for deburring, milling, grinding and cutting, also in hard-to-reach places
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Long grinding spindle - ideal for working on hard to reach places
- Precise collar for stationary use
- Removable protective rubber cap for comfortable and safe working
- Slim design for ideal handling

Technical data

Characteristics

No-load speed	30000 rpm
Rated input power	400 W
Output power	250 W
Speed at rated load	12400 rpm
Collar diameter	43 mm / 1 11/16 "
Collet chuck bore	6.35 mm / 1/4 "
Weight (without power cable)	1.5 kg / 3.3 lbs
Cable length	2.55 m / 8 ft

Vibration

Surface grinding (up to Ø 25 mm)	6.6 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Surface grinding (up to Ø 50 mm)	19.9 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	79 dB(A)
Sound power level (LwA)	90 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Collet 1/4"
 Protective rubber cap
 2 Open-jawed spanners