

GP 400 (601053420) Die grinder
(110-120 V / AC/DC 0/50/60 Hz); Cardboard box

Order no. 601053420
EAN 4061792257610



Product may differ from Image



- Robust die grinder for deburring, milling, grinding and cutting, also in hard-to-reach places
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Long grinding spindle - ideal for working on hard to reach places
- Precise collar for stationary use
- Removable protective rubber cap for comfortable and safe working
- Slim design for ideal handling

Technical data**Characteristics**

| | |
|------------------------------|-------------------|
| No-load speed | 30000 rpm |
| Rated input power | 400 W |
| Output power | 250 W |
| Speed at rated load | 12400 rpm |
| Collar diameter | 43 mm / 1 11/16 " |
| Collet chuck bore | 6.35 mm / 1/4 " |
| Weight (without power cable) | 1.5 kg / 3.3 lbs |
| Cable length | 2.55 m / 8 ft |

Vibration

| | |
|----------------------------------|-----------------------|
| Surface grinding (up to Ø 25 mm) | 6.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Surface grinding (up to Ø 50 mm) | 19.9 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 79 dB(A) |
| Sound power level (LwA) | 90 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Collet 1/4"
Protective rubber cap
2 Open-jawed spanners