

WEP 17-150 Quick RT (601078420) Angle grinder (110-120 V / 60 Hz); Cardboard box

Order no. 601078420 EAN 4007430314345



Product may differ from Image

















- Maximum productivity thanks to top performance with low weight
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Metabo Longlife-motor with new cooling and carbon brush system for twice the service life
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data		
Characteristics		
Disc-Ø	150 mm // 6 "	
Output power	1030 W	
No-load speed	9600 rpm	
Speed at rated load	9600 rpm	
Torque	4.4 Nm / 39 in-lbs	
Spindle thread	5/8" - 11 UNC	
Handle circumference	138 mm / 5.438 "	
Weight (without power cable)	2.5 kg / 5.6 lbs	
Cable length	2.5 m / 8 ft	
Vibration		
Surface grinding	8.2 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Grinding with sandpaper	4 m/s ²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	94 dB(A)	
Sound power level (LwA)	105 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Inner support flange

M-Quick flange nut

www.metabo.com 2/2