

Power 400-20 W OF (601546000) Compressor (230 V / 50 Hz); Cardboard box

Order no. 601546000
EAN 4007430244888



Product may differ from Image



- Compact and mobile piston compressor for flexible use both indoors and on construction sites
- Particularly low-level noise and vibrations
- For single phase alternating current
- Designed for continuous operation with S1 motor operating mode
- Oil-free piston compressor: simple transportation and reduced service requirements
- Operating pressure can be regulated according to application by means of a pressure reducer and manometer
- Fittings and control elements protected in tubular frames and clearly visible
- Rubberised, stable wheels and pull handle for mobile use
- Cable winding mechanism
- Convenient pressure switch for good cold starting, complete with relief valve
- Overload protection: protects the motor from overheating
- Rubberised feet for optimum stability
- Attachment and transport option for Metaloc and other common storage case systems
- Crane eyelet for safe and easy transport on the construction site

Technical data

Characteristics

Suction rate	330 l/min / 87 gal/h
Filling capacity	200 l/min / 7.1 cfm
Effective delivery volume (at 80% max. pressure)	185 l/min / 6.5 cfm
Maximum pressure	10 bar / 145 psi
Rated input power	2.2 kW / 3 HP
Maximum speed	1400 rpm
Tank capacity	20 l / 5.3 gal
Sound pressure level (LpA)	78 dB(A)
Sound power level (LwA)	95 dB(A)
Dimensions	580 x 600 x 500 mm // 1.9 x 2 x 1.7 ft
Weight	47 kg / 103.6 lbs
Cable length	4 m / 13 ft

Noise emission

Sound pressure level	78 dB(A)
Sound power level (LwA)	95 dB(A)

Scope of delivery

2 Universal quick-action couplings