

KHE 2445 (601709590) Combination hammer (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 601709590
EAN 4061792219472



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation

Technical data

Characteristics

Max. single blow energy (EPTA)	2.4 J
Maximum impact rate	4800 bpm
Rated input power	800 W
Drill-Ø concrete with hammer drills	24 mm / 1 "
Drill-Ø masonry with core bits	82 / 3 7/32
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-load speed	0 - 1500 rpm
Speed at rated load	1050 rpm
Bit retainer	SDS-plus
Collar diameter	43 mm / 1.69 "
Weight (without power cable)	2.8 kg / 6.17 lbs
Cable length	4 m / 157 1/2 "

Vibration

Hammer drilling concrete	12.8 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	11.1 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	90 dB(A)
Sound power level (LwA)	101 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

rubber-coated side handle
 Drilling depth guide
 Plastic carry case