

## KHE 2645 (601710500) Combination hammer Plastic Carry Case

Order no. 601710500 EAN 4061792213203



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation

www.metabo.com 1/2



| Technical data                      |                       |
|-------------------------------------|-----------------------|
| Characteristics                     |                       |
| Max. single blow energy (EPTA)      | 2.9 J                 |
| Maximum impact rate                 | 4300 bpm              |
| Rated input power                   | 850 W                 |
| Drill-Ø concrete with hammer drills | 26 mm / 1 "           |
| Drill-Ø masonry with core bits      | 82 mm / 3 7/32 "      |
| Drill Ø steel                       | 13 mm / 1/2 "         |
| Drill-Ø soft wood                   | 30 mm / 1 3/16 "      |
| No-load speed                       | 0 - 1150 rpm          |
| Speed at rated load                 | 850 rpm               |
| Bit retainer                        | SDS-plus              |
| Collar diameter                     | 50 mm / 2 "           |
| Weight (without power cable)        | 2.9 kg / 6.39 lbs     |
| Cable length                        | 4 m / 13 ft           |
| Vibration                           |                       |
| Hammer drilling concrete            | 16.9 m/s²             |
| Uncertainty of measurement K        | 1.5 m/s²              |
| Chiseling                           | 10.1 m/s <sup>2</sup> |
| Uncertainty of measurement K        | 1.5 m/s²              |
| Noise emission                      |                       |
| Sound pressure level                | 92 dB(A)              |
| Sound power level (LwA)             | 103 dB(A)             |
| Uncertainty of measurement K        | 3 dB(A)               |

## Scope of delivery

rubber-coated side handle

Drilling depth guide

Plastic carry case

www.metabo.com 2 / 2