

KH 18 LTX BL 24 (601713660) Cordless hammer 18V 2x5.5Ah LiHD; Charger ASC 145; metaBOX 165 L

Order no. 601713660
EAN 4061792218536



Product may differ from Image



- Very lightweight, compact cordless hammer with brushless motor for low-fatigue drilling in any working position
- Maximum drill performance, efficiency and service life thanks to brushless technology and high-performance hammer action
- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Electronic soft start for precise spot-drilling
- Safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- LED work light for optimum view of the drilling site
- Dust-free drilling with external dust extraction ESA plus (accessory)
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|-------------------------------------|-------------------|
| Type of battery pack | LiHD |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 5.5 Ah |
| Max. single blow energy (EPTA) | 2.2 J |
| Maximum impact rate | 4750 bpm |
| Drill-Ø concrete with hammer drills | 24 mm / 1 " |
| Drill-Ø masonry with core bits | 82 mm / 3 7/32 " |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 30 mm / 1 3/16 " |
| No-load speed | 0 - 1280 rpm |
| Bit retainer | SDS-plus |
| Weight without battery pack | 2.7 kg / 5.95 lbs |

Vibration

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 13.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 9.2 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 90 dB(A) |
| Sound power level (LwA) | 101 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

rubber-coated side handle
 Quick charger ASC 145 "AIR COOLED"
 metaBOX 165 L
 Drilling depth guide
 2 LiHD battery packs (18 V/5.5 Ah)