

KH 18 LTX BL 28 Q Set ISA (601715930) Cordless hammer

18V 2x5.5Ah LiHD; Charger ASC 145 (220-240 V / -); metaBOX 185 XL; with integrated dust extraction and Metabo Quick chuck

Order no. 601715930

EAN 4061792218642



Product may differ from Image



- Extremely light and compact cordless hammer with integrated extraction interface
- Maximum drill performance, efficiency and service life thanks to brushless technology and high-performance hammer action
- Dust-free drilling with compact dust extraction ISA 28
- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for many different applications
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Optional reduction of speed and impact energy for starting a drill hole or working in softer materials
- Electronic soft start for precise spot-drilling
- Double safety when the drill bit jams: No kick-back thanks to the mechanic decoupling plus ultra-fast sensor-controlled shutdown
- LED work light for optimum view of the drilling site
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

Type of battery pack	LiHD
Battery voltage	18 V
Battery pack capacity	2 x 5.5 Ah
Max. single blow energy (EPTA)	3 J
Maximum impact rate	4470 bpm
Drill-Ø concrete with hammer drills	28 mm / 1 3/32 "
Drill-Ø masonry with core bits	82 mm / 3 7/32 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-load speed	0 - 1000 rpm
Bit retainer	SDS-plus
Weight without battery pack	4.5 kg / 7.5 lbs

Vibration

Hammer drilling concrete	18.2 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	13.4 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Integrated dust extraction ISA 28
 Keyless chuck for tools with cylindrical shank
 rubber-coated side handle
 Drilling depth guide
 2 LiHD battery packs (18 V/5.5 Ah)
 Quick charger ASC 145 "AIR COOLED"
 metaBOX 185 XL
 Replacement extraction head
 Hammer chuck for tools with SDS-plus shank end