

KHE 2845 (601739500) Combination hammer Plastic Carry Case

Order no. 601739500 EAN 4061792227958



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation

www.metabo.com 1/2



Technical data	
Characteristics	
Max. single blow energy (EPTA)	3 J
Maximum impact rate	4400 bpm
Rated input power	880 W
Drill-Ø concrete with hammer drills	28 mm / 1 3/32 "
Drill-Ø masonry with core bits	82 mm / 3 7/32 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-load speed	0 - 1200 rpm
Speed at rated load	850 rpm
Bit retainer	SDS-plus
Collar diameter	50 mm / 2 "
Weight (without power cable)	2.9 kg / 6.39 lbs
Cable length	4 m / 13 ft
Vibration	
Hammer drilling concrete	16.9 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	10.1 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

rubber-coated side handle

Drilling depth guide

Plastic carry case

www.metabo.com 2 / 2