

WPBA 18 LTX BL 15-150 Quick DS (601745840) Cordless angle grinder 18V; metaBOX 165 L; with brake, quick-locking nut

Order no. 601745840
EAN 4061792247239



Product may differ from image



- Brushless cordless angle grinder of the new generation: the most powerful one in its class, as powerful as a 1,500 Watt mains-powered tool
- Service-free Brushless motor with highest efficiency and maximum handiness
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Fast brake system for highest user safety: Disc stops within 1.5 seconds after switching off
- Best anti-vibration system: integrated auto-balancer for less hand-arm vibrations, longer service life of the machine and up to twice the service life of the grinding wheels
- M-Quick System for tool-free disc change at the touch of a button
- Safety bracket DS for the attachment of a tool safety strap when working at great heights
- Tool-free adjustable guard; twist-proof
- Battery pack can be rotated in 90° steps for best ergonomics in any working position
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety
- Electronic overload protection, soft start and restart protection
- Detachable dust protection filter protects motor from coarse particles
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|-----------------------------|-----------------|
| Battery voltage | 18 V |
| Disc-Ø | 150 mm / 6 " |
| Max. cutting depth | 46 mm / 1.811 " |
| No-load speed | 10000 rpm |
| Spindle thread | M 14 |
| Handle circumference | 166 |
| Weight without battery pack | 2.2 kg |
| Weight with battery pack | 2.9 kg |

Vibration

| | |
|------------------------------|-----------------------|
| Surface grinding | 7.52 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|---------|
| Uncertainty of measurement K | 3 dB(A) |
|------------------------------|---------|

Scope of delivery

Guard
 Metabo VibraTech (MVT) side handle
 Dust Protection Filter
 Safety bracket DS
 metaBOX 165 L
 without battery pack, without charger
 Inner support flange
 M-Quick flange nut