

## BS 18 LTX Quick (602193840) Cordless drill / screwdriver 18V; metaBOX 145 L

Order no. 602193840  
EAN 4007430287007



Product may differ from Image



- Robust drill/screwdriver with maximum power for demanding applications
- Metabo quick system: quick exchange of chucks, bit holders, angle adapters and more for flexible work
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Robust, durable gear housing made from aluminium die-cast
- Spindle with magnetic hexagon recess for screwdriver bits for working without chuck
- Powerful Metabo 4-pole motor for fast drilling and screwdriving
- Overload protection: protects the motor from overheating
- Euro collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Handy belt hook, can be fixed either on the right or left side
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                                |
|-----------------------------|--------------------------------|
| Battery voltage             | 18 V                           |
| Maximum torque, soft        | 55 Nm / 487 in-lbs             |
| Pulse torque                | 60 Nm / 531 in-lbs             |
| Maximum torque, hard        | 110 Nm / 974 in-lbs            |
| Adjustable torque           | 1.5 - 24 Nm // 13 - 212 in-lbs |
| Drill Ø steel               | 13 mm / 1/2 "                  |
| Drill-Ø soft wood           | 65 mm / 2 1/2 "                |
| No-load speeds              | 0 - 500 / 0 - 1700 rpm         |
| Chuck capacity              | 1.5 - 13 mm // 1/16 - 1/2 "    |
| Collar diameter             | 43 mm / 1 11/16 "              |
| Weight without battery pack | 1.7 kg / 3.7 lbs               |
| Weight with battery pack    | 2.1 kg / 4.6 lbs               |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Drilling in metal            | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Screwdriving without impact  | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 80 dB(A) |
| Sound power level (LwA)      | 91 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Quick-change chuck  
 Belt hook  
 metaBOX 145 L  
 without battery pack, without charger  
 Quick-change bit holder  
 Side handle