

SB 18 LTX BL I (602352600) Cordless hammer drill 18V 2x5.2Ah Li-ion; Charger ASC 55 (110-120 V / 50 - 60 Hz); metaBOX 145 L

Order no. 602352600 EAN 4007430297969



Product may differ from Image









- Brushless hammer drill with maximum power for demanding applications
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- High-performance impact mechanism for optimum drilling performance
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- With handy belt hook and bit case which can be fixed either on the right or left side
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.
- With metaBOX, the intelligent solution for transport and storage

www.metabo.com 1/2



Technical data		
Characteristics		
Type of battery pack	Li-ion	
Battery voltage	18 V	
Battery pack capacity	2 x 5.2 Ah	
Maximum torque, soft	60 Nm / 531 in-lbs	
Pulse torque	65 Nm / 48 ft. lbs	
Maximum torque, hard	120 Nm / 1062 in-lbs	
Adjustable torque	1 - 20 Nm // 9 - 177 in-lbs	
Drill-Ø masonry	16 mm / 5/8 "	
Drill Ø steel	13 mm / 1/2 "	
Drill-Ø soft wood	65 mm / 2 1/2 "	
No-load speed	0 - 500 / 0 - 1850 rpm	
Maximum impact rate	32300 bpm	
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "	
Weight with battery pack	2.4 kg / 5.3 lbs	
Vibration		
Drilling in metal	3.2 m/s ²	
Uncertainty of measurement K	1.5 m/s ²	
Impact drilling concrete	20.7 m/s ²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	92 dB(A)	
Sound power level (LwA)	103 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Futuro Plus keyless chuck with metal sleeve 2 Li-Power battery packs (18 V/5.2 Ah) Charger ASC 55 "AIR COOLED" metaBOX 145 L Side handle Belt hook and bit case

www.metabo.com 2/2