

## SB 18 LTX BL I (602360840) Cordless hammer drill 18V; metaBOX 145 L

Order no. 602360840  
EAN 4061792188181



Product may differ from Image



- Brushless hammer drill with maximum power for demanding applications
- Hammer drill function for drilling in masonry
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

Battery voltage	18 V
Maximum torque, soft	65 Nm / 575 ft. lbs
Pulse torque	65 Nm / 575 in-lbs
Maximum torque, hard	130 Nm / 1151 ft. lbs
Adjustable torque	1 - 20 Nm // 9 - 177 in-lbs
Drill-Ø masonry	16 mm / 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	68 mm / 2.68 "
No-load speed	0 - 550 / 0 - 2000 rpm
Maximum impact rate	38000 bpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Collar diameter	43 mm / 1 11/16 "
Weight without battery pack	1.8 / 4
Weight with battery pack	2.2 kg / 4.9 lbs

### Vibration

Drilling in metal	2.6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Impact drilling concrete	16.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.7 m/s <sup>2</sup>

### Noise emission

Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Keyless chuck  
metaBOX 145 L  
Side handle  
Belt hook and bit case