

BS 18 LTX-3 BL Q I Metal (603180620) Cordless drill / screwdriver 18V 2x5.5Ah LiHD; Charger ASC 145 (110-120 V / -); metaBOX 145 L

Order no. 603180620
EAN 4061792211674



Product may differ from Image



- The metal expert: brushless, 3-speed drill with maximum power and automatically re-tightening chuck
- Extremely powerful chuck with re-tensioning function against slipping of the bit and high degree of concentricity
- Third speed setting with high torque (max. 4,000/min) for extended range of application and even faster drilling progress, especially in metal
- Metabo QuickPlus System: quick change of chucks, bit holders, angle adapters and more for flexible working with maximum load
- Precision Stop: electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Euro collar (Ø 43 mm) for versatile use
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|-----------------------------|-----------------------------------|
| Type of battery pack | LiHD |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 5.5 Ah |
| Maximum torque, soft | 65 Nm / 575 in-lbs |
| Maximum torque, hard | 130 Nm / 1150 in-lbs |
| Adjustable torque | 1 - 18 Nm // 8.9 - 159.3 in-lbs |
| Drill Ø steel | 16 mm / 5/8 " |
| Drill-Ø soft wood | 68 mm / 2.68 " |
| No-load speeds | 0 - 450 / 0 - 2000 / 0 - 4000 rpm |
| Chuck capacity | 1.5 - 13 mm // 1/16 - 1/2 " |
| Collar diameter | 43 mm / 1.69 " |
| Weight without battery pack | 2 kg / 4.4 lbs |
| Weight with battery pack | 3 kg / 6.6 lbs |

Vibration

| | |
|------------------------------|----------------------|
| Drilling in metal | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 75 dB(A) |
| Sound power level (LwA) | 85 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Futuro Top quick-change chuck "QuickPlus"
 2 LiHD battery packs (18 V/5.5 Ah)
 Quick charger ASC 145 "AIR COOLED"
 metaBOX 145 L
 Side handle
 C-wrench