

## SB 18 LTX-3 BL I Metal (603183840) Cordless hammer drill 18V; metaBOX 145 L

Order no. 603183840  
EAN 4061792211698



Product may differ from Image



- The metal expert: brushless 3-speed cordless hammer drill with maximum power and automatically re-tightening chuck
- Extremely powerful chuck with re-tensioning function against slipping of the bit and high degree of concentricity
- Third speed setting with high torque (max. 4,000/min) for extended range of application and even faster drilling progress, especially in metal
- Hammer drill function for drilling in masonry
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Overload protection: protects the motor from overheating
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                                   |
|-----------------------------|-----------------------------------|
| Battery voltage             | 18 V                              |
| Maximum torque, soft        | 65 Nm / 575.3 in-lbs              |
| Maximum torque, hard        | 130 Nm / 1150.6 in-lbs            |
| Adjustable torque           | 1 - 18 Nm // 8.9 - 159.3 in-lbs   |
| Drill-Ø masonry             | 16 mm / 5/8 "                     |
| Drill Ø steel               | 16 mm / 5/8 "                     |
| Drill-Ø soft wood           | 68 mm / 2.68 "                    |
| No-load speed               | 0 - 450 / 0 - 2000 / 0 - 4000 rpm |
| Maximum impact rate         | 38000 bpm                         |
| Chuck capacity              | 1.5 - 13 mm // 1/16 - 1/2 "       |
| Collar diameter             | 43 mm / 1.69 "                    |
| Weight without battery pack | 2 kg / 4.4 lbs                    |
| Weight with battery pack    | 3 kg / 6.6 lbs                    |

### Vibration

|                              |          |
|------------------------------|----------|
| Drilling in metal            | 3 m/s²   |
| Uncertainty of measurement K | 1.5 m/s² |
| Impact drilling concrete     | 25 m/s²  |
| Uncertainty of measurement K | 1.5 m/s² |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 98 dB(A)  |
| Sound power level (LwA)      | 109 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Futuro Top keyless chuck  
 metaBOX 145 L  
 without battery pack, without charger  
 Side handle  
 C-wrench