

## WA 13-125 Quick (603630000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 603630000

EAN 4061792176324



Product may differ from Image



- Long service life for demanding applications: powerful and robust angle grinder with highest power density in its class for quick work progress
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Best anti-vibration system: integrated auto-balancer for up to 50% less hand-arm vibrations, longer service life of the machine and up to twice the service life of the grinding wheels
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Restart protection after power interruption
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

**Technical data****Characteristics**

|                              |                      |
|------------------------------|----------------------|
| Disc-Ø                       | 125 mm // 5 "        |
| Rated input power            | 1350 W               |
| Output power                 | 830 W                |
| No-load speed                | 11000 rpm            |
| Speed at rated load          | 8000 rpm             |
| Torque                       | 3.4 Nm / 30.1 in-lbs |
| Spindle thread               | M 14                 |
| Handle circumference         | 206 mm / 8 1/8 "     |
| Weight (without power cable) | 2.4 kg / 5.3 lbs     |
| Cable length                 | 4 m / 13 ft          |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 4 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 3 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

**Noise emission**

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 94 dB(A)  |
| Sound power level (LwA)      | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

**Scope of delivery**

Guard  
Metabo VibraTech (MVT) side handle  
Inner support flange  
M-Quick flange nut