

WEA 24-230 MVT Quick (606472000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box; with quick-locking nut, rotating main handle

Order no. 606472000 EAN 4007430268259



Product may differ from Image















- Metabo Marathon motor with patented dust protection for long service life
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Reduced vibrations for low-fatigue working thanks to Metabo VibraTech (MVT) damping system and integrated Auto-
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic overload protection and restart protection
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor
- LED signal indicates triggered restart protection or overheating

www.metabo.com 1/2



Technical data	
Characteristics	
Disc-Ø	230 mm // 9 "
Rated input power	2400 W
Output power	1600 W
No-load speed	6600 rpm
Speed at rated load	4600 rpm
Torque	17 Nm / 150 in-lbs
Spindle thread	M 14
Handle circumference	144 mm / 5.669 "
Weight (without power cable)	5.9 kg / 13 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	4.5 m/s ²
Uncertainty of measurement K	1.5 m/s²
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)

Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Inner support flange

Quick-locking nut

www.metabo.com 2 / 2