

WEPB 24-230 MVT (606479420) Angle grinder (110-120 V / 50 - 60 Hz); Cardboard box; with mechanical disc brake

Order no. 606479420 EAN 4007430337917



Product may differ from Image















- Metabo Long-life motor with patented dust protection for long service life
- Highest degree of user safety thanks to mechanical disc brake and deadman's switch: disc stop in 2.5 seconds after releasing even in case of a power cut
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic overload protection and restart protection
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor
- LED signal indicates triggered restart protection or overheating

www.metabo.com 1/2



Technical data	
Characteristics	
Disc-Ø	230 mm // 9 "
No-load speed	6600 rpm
Speed at rated load	4600 rpm
Torque	17 Nm / 150 in-lbs
Spindle thread	5/8" - 11 UNC
Handle circumference	149 mm / 5.866 "
Weight (without power cable)	6 kg / 13.2 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	6.3 m/s²
Uncertainty of measurement K	1.5 m/s²
Grinding with sandpaper	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

www.metabo.com 2/2