

HS 8875 (608875180) Hedge trimmer (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 608875180

EAN 4007430180902



Product may differ from Image



- Double reduction gearing for particularly high cutting performance
- Patented Metabo handle system with additional switch for up to 50% more reach and range
- Low weight avoids fatigue when working
- Patented mechanical quick blade stop (in 0.05 seconds) for improved safety
- Blades with special geometry generate less wear and thus deliver 200% longer service life
- Clean cut thanks to diamond-ground blade teeth on both sides at a 30° angle
- Lower safety blade for high safety at work
- Metabo S-automatic safety clutch: Protects blades and gears when debris or large branches stop the blades
- Fatigue-proof operation due to ergonomic full grip bow-type handle design and optimum centre of gravity position
- Very quiet running due to shear blades running in opposite direction
- User-friendly guidance of machine exhaust in all working situations
- Particularly easy to service thanks to carbon brush and cable replacement cover
- Cable strain relief prevents the unintentional disconnection of the plug-in connection
- Trigger guard with twig feed protects user and gear from kickbacks

Technical data**Characteristics**

Max. cutting thickness	26 mm / 1 "
Cutting length	75 cm / 30 "
Blade clearance	34 mm / 1 3/8 "
Number of strokes (No Load)	2900 spm
Rated input power	660 W
Weight (without power cable)	4.4 kg / 9.7 lbs
Cable length	0.5 m / 2 ft

Vibration

Idle	3.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	84 dB(A)
Sound power level (LwA)	95 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Trigger guard
Container