

KS 18 LTX 57 BL (611857810) Cordless circular saw 18V 2x8Ah LiPOWER / LiHD; Charger ASC 145; metaBOX 340

Order no. 611857810
EAN 4061792237179



Product may differ from Image



- Powerful, light, cordless circular saw for universal use on construction sites
- Powerful Brushless motor for quick work progress and highest efficiency
- Aluminium base plate can be directly used on guide rails from Metabo and Mafell, Bosch, Festool, Makita, HiKOKI, Hilti and other manufacturers
- Fast, precise cross cuts thanks to easy coupling with a Metabo cross cutting rail
- Automatic switching on/off of the connected vacuum cleaner thanks to CordlessControl. (available as accessory)
- Fast brake stops the saw blade quickly and improves safety
- Accurately angled bevel cuts down to 50°, with handy snap-in point at 45°
- 0° position re-adjustable for highest cutting precision
- Clearly visible cutting indicator for precise sawing after initial cut
- Handle with non-slip soft-grip surface for safe guidance
- Lower weight and compact, ergonomic design
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|------------------------------------|-------------------------------|
| Type of battery pack | LiPOWER / LiHD |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 8 Ah |
| Swivel range from / to: | 0 / + 50 ° |
| Adjustable cutting depth | 0 - 57 mm // 0 - 2 1/4 " |
| Maximum cutting depth at 90° | 57 mm / 2 1/4 " |
| Maximum cutting depth at 45° | 43 mm / 1 11/16 " |
| Max. cutting depth with guide rail | 52 mm / 2 1/16 " |
| Saw blade Ø x bore | 165 x 20 mm // 6 1/2 x 0.78 " |
| No-load speed | 5000 rpm |
| Max. cutting speed | 43 m/s / 142 ft/s |
| Weight without battery pack | 2.7 kg / 5.9 lbs |
| Weight with battery pack | 3.6 kg / 7.9 lbs |

Vibration

| | |
|------------------------------|----------|
| Sawing chipboards | 1 m/s² |
| Uncertainty of measurement K | 1.5 m/s² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 94 dB(A) |
| Sound power level (LwA) | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Carbide circular saw blade (18 teeth)
 2 LiHD Battery packs (18 V/8.0 Ah)
 Quick charger ASC 145 "AIR COOLED"
 Metabox
 Parallel guide
 Hexagonal wrench