

## MT 18 LTX Compact (613021510) Cordless multi-tool 18V 2x2Ah LiPOWER; Charger ASC 55 (220-240 V / 50 - 60 Hz); metaBOX 145 L

Order no. 613021510  
EAN 4007430277534



Product may differ from Image



- Oscillating cordless multi-tool with high performance comparable to that of a mains powered version
- Indispensable for interior development such as cutting, sanding and scraping of different materials
- Tool holder for maximum compatibility to OIS, Starlock and other accessories
- Metabo Quick tool change system for time-saving, convenient change of accessories
- Quick work progress thanks to large oscillation angle and VTC-Electronics to maintain constant speed even under load
- Slim design and non-slip soft-grip surface for optimised handling
- Extra bright LED lights for good visibility of the working area
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

Type of battery pack	LiPOWER
Battery voltage	18 V
Battery pack capacity	2 x 2 Ah
Orbital frequency with no load	7000 - 18000 rpm
Oscillation angle left/right	1.6 °
Bit retainer	Compatible with OIS and Starlock
Base plate, dimensions from corner to corner	93 mm / 3 5/8 "
Weight without battery pack	1.4 kg / 3.1 lbs
Weight with battery pack	1.8 kg / 4 lbs

### Vibration

Surface grinding	7.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Scraping	11.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Sawing with plunge cut saw blade	13 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Sawing with segmented sawing blade	11.6 m/s <sup>2</sup>
Uncertainty of measurement K	3 m/s <sup>2</sup>

### Noise emission

Sound pressure level	77 dB(A)
Sound power level (LwA)	88 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Plunge saw blade 32 mm HCS (wood)  
 Triangular hook and loop sanding plate 93 mm  
 5 Hook and loop sanding sheets 93 mm P 80  
 5 Hook and loop sanding sheets 93 mm P 120  
 Suction Adapter  
 2 Li-Power battery packs (18 V/2.0 Ah)  
 Charger ASC 55 "AIR COOLED"  
 metaBOX 145 L  
 Segment saw blade 85 mm BiM (wood + metal)  
 Scraping knife, rigid 52 mm HCS