

WEF 9-125 (613060420) Flat-head angle grinder (110-120 V / 50 - 60 Hz); Cardboard box

Order no. 613060420 EAN 4007430240545



Product may differ from Image











- Most compact flat-head angle grinder for working at acute angles down to 43°
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Metabo Long-life motor with patented dust protection for long service life
- Constamatic (C)-Full wave electronics: fast work progress by means of almost constant speed under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Electronic overload protection, soft start and restart protection
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



| Technical data | | |
|------------------------------|----------------------|--|
| Characteristics | | |
| Minimum accessible angle | 43 ° | |
| Disc-Ø | 125 mm / 5 " | |
| Rated input power | 910 W | |
| Output power | 430 W | |
| No-load speed | 10000 rpm | |
| Speed at rated load | 8200 rpm | |
| Torque | 2 Nm / 18 in-lbs | |
| Spindle thread | 5/8" - 11 UNC | |
| Weight (without power cable) | 2.1 kg / 4.6 lbs | |
| Cable length | 4 m / 13 ft | |
| Handle circumference | 197 mm / 7 3/4 " | |
| Vibration | | |
| Surface grinding | 5.5 m/s ² | |
| Uncertainty of measurement K | 1.5 m/s² | |
| Grinding with sandpaper | 2.5 m/s² | |
| Uncertainty of measurement K | 1.5 m/s² | |
| Noise emission | | |
| Sound pressure level | 88 dB(A) | |
| Sound power level (LwA) | 99 dB(A) | |
| Uncertainty of measurement K | 3 dB(A) | |

Scope of delivery

Guard

Flat-pin spanner

Side handle

1 Flap disc Flexiamant Super Convex (125mm; P60)

Inner support flange

Nut with two holes

www.metabo.com 2/2