

WPF 18 LTX 125 (613070860) Cordless flat-head angle grinder 18V; Cardboard box

Order no. 613070860 EAN 4007430244680



Product may differ from Image



- Cordless angle grinder with extremely low gear head for working in acute angles down to 43°
- Compact design for quick removal of welding slag, rust or paint in tight places e.g. frame constructions
- Low-fatigue working even on weld seams in difficult to access places thanks to slim handle
- Paddle switch with deadmans function: safe to operate due to an ergonomically integrated non-slip switch
- Robust motor for long service life
- Tool-free adjustable guard; twist-proof
- Battery pack can be swivelled for better working in hard to reach places
- Detachable dust filter protects motor from coarse particles
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| Type of battery pack | LiPOWER |
|------------------------------|----------------------|
| Battery voltage | 18 V |
| Minimum accessible angle | 43 ° |
| Disc-Ø | 125 mm / 5 " |
| No-load speed | 8000 rpm |
| Spindle thread | 5/8" - 11 UNC |
| Weight without battery pack | 2 kg / 4.4 lbs |
| Weight with battery pack | 2.7 kg / 6 lbs |
| Vibration | |
| Surface grinding | 4.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 83 dB(A) |
| Sound power level (LwA) | 94 dB(A) |
| | |

Scope of delivery

5 Flap discs Flexiamant Super Convex (125mm; P60) Nut with two holes Side handle Dust Protection Filter Flat-pin spanner without battery pack, without charger Guard Inner support flange