

TKHS 315 M - 3,1 WNB (0103153100) Table saw
(220-240 V / 50 - 60 Hz); Cardboard box

Order no. 0103153100
 EAN 4003665403403



Product may differ from Image



- Restart protection: prevents unintentional start-up after power supply interruption
- Precise, powerful table saw in professional configuration – quick to adapt for every application
- Ideal for sawing squared timber, boards, panels and wood-like materials in the workshop and at construction sites
- Quiet induction motor with motor brake and overload protection - maintenance-free and robust.
- Mitre fence with linear stop, can also be used a sliding table
- Sturdy rip fence with quick fastening
- Freely height-adjustable saw blade
- Comfortable setting of the saw blade inclination from the front
- Sturdy, powder-coated sheet steel design and galvanised table-top
- Foldable table length extension
- Frame and motor pre-mounted

Technical data

Characteristics

| | |
|---------------------------------------|--|
| Dimensions | 1700 x 700 x 1000 mm // 5.6 x 2.3 x 3.3 ft |
| Max. support surface | 800 x 600 mm // 31 1/2 x 23 5/8 " |
| Working height | 850 mm // 33 1/2 " |
| Cutting height | 0 - 85 mm // 0 - 3 5/16 " |
| Maximum cutting height 90/45° | 85 / 53 mm // 3 5/16 / 2 1/16 " |
| Maximum cutting width at rip fence | 340 mm / 13 3/8 " |
| Maximum material width at mitre fence | 250 mm / 9 13/16 " |
| No-load speed | 2990 rpm |
| Cutting speed | 50 m/s / 164 ft/s |
| Saw blade | 315 x 30 mm // 12 3/8 x 1.181 " |
| Saw blade swivel range | 0 - 45 ° |
| Mains voltage | 220 - 240 V |
| Rated input power | 3100 W |
| Weight | 75 kg / 165 lbs |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 97 dB(A) |
| Sound power level (LWA) | 106 dB(A) |
| Uncertainty of measurement K | 4 dB(A) |

Scope of delivery

Carbide saw blade with alternately bevel-ground tips (24 teeth)
 Mitre Fence
 Table extension (600 x 800 mm)
 Chip and Dust Extraction Unit
 Push stick
 Wheel set incl. handles
 Rip Fence