

TBP 5000 M (0250500050) Deep Well Pump
(220-240 V / 50 Hz); Cardboard box

Order no. 0250500050
EAN 4003665425948



Product may differ from Image



- Especially suitable for great depths, as in bore wells and shafts
- For garden irrigation and groundwater pumping, as well as pumping, pumping empty, pumping dry and circulation of clear water
- Overload protection: protects the motor from overheating
- Integrated check valve prevents dry running of the pump when it is switched off, enabling a short restart process
- Robust pump head with brass thread insert and fixing eyelets for the drain rope
- Suitable for bore wells of 100 mm Ø (4")
- 8-level pump running gear for particularly high pump capacity
- Pump housing made of stainless steel
- 22m Connection cable for more immersion depth

Technical data**Characteristics**

Rated input power	1000 W
Maximum delivery rate	5000 l/h / 1321 gal/h
Maximum delivery height	60 m / 197 ft
Maximum pressure	6 bar / 87 psi
Maximum immersion depth	20 m / 65.6 ft
Discharge port	1" female thread
Pump housing	Stainless steel
Pump diameter	98 mm
Protection type IP	IP X8
Number of impellers	8
Dimensions	98 x 98 x 920 mm / 3 7/8 x 3 7/8 x 36 7/32 "
Weight	12.2 kg / 26.9 lbs
Cable length	22 m / 72 ft

Scope of delivery

-