

PS 15000 S (0251500000) Dirty water submersible pump (220-240 V / 50 Hz); Cardboard box

Order no. 0251500000 EAN 4003665502304



Product may differ from Image



- For pumping empty, pumping dry and circulating fresh water or dirty water from containers, tanks or flooded cellars
- Double seal system for protection of the pump if the water is particularly dense or contains large particles
- Overload protection: protects the motor from overheating
- Adjustable float switch for automatic mode
- Robust housing made of impact-proof plastic
- Ergonomic handle for comfortable transport

www.metabo.com 1/2



| Technical data | |
|-----------------------------|---|
| Characteristics | |
| Rated input power | 850 W |
| Maximum delivery rate | 15000 l/h / 3963 gal/h |
| Maximum delivery height | 9.5 m / 31 ft |
| Maximum pressure | 0.95 bar / 13.8 psi |
| Maximum immersion depth | 5 m / 16.4 ft |
| Discharge port | 1 1/4" female thread |
| Pump housing | Plastic |
| Protection type IP | IP X8 |
| Maximum particle size up to | 30 mm / 1 3/16 " |
| Number of impellers | 1 |
| Dimensions | 257 x 200 x 345 mm // 10 1/8 x 7 7/8 x 13 19/32 " |
| Weight | 6.5 kg / 14.3 lbs |
| Cable length | 10 m / 33 ft |

Scope of delivery

Angle connection piece with multi-adapter Float switch

www.metabo.com 2/2