

MHE 5 (600148500) Chipping hammer (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 600148500
EAN 4061792199231



Product may differ from Image



- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Vario-Constamatic (VC)-Full wave electronics for working at impact rates to suit the application materials, and that remain almost constant even under load
- Thumbwheel for preselection of impact rate
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Optimum heat dissipation and low weight thanks to die cast magnesium gear housing
- Lockable switch for comfortable chiselling in continuous operation
- Service display, e.g. to indicate when the carbon brush needs to be replaced, and an LED indicating mains voltage
- Early warning system thanks to service LED for targeted planning of the carbon brush replacement 8 working hours before switching off
- The adjustable front handle can be rotated 360° and the angle adjusted for an optimum working position

Technical data**Characteristics**

Max. single blow energy (EPTA)	7.1 J
Maximum impact rate	3000 bpm
Rated input power	1100 W
Bit retainer	SDS-max
Weight (without power cable)	5.7 kg
Cable length	6 m / 19.685 ft

Vibration

Chiseling	12.3 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	95 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	1.67 dB(A)

Scope of delivery

Front handle
Plastic carry case
Lubricant for tool shank end
Duster