

W 9-125 Quick (600374000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box; with quick-locking nut

Order no. 600374000 EAN 4007430240989



Product may differ from Image



- Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Restart protection after power interruption
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

| Disc-Ø | 125 mm // 5 " |
|--|----------------------|
| Rated input power | 900 W |
| Output power | 550 W |
| No-load speed | 10500 rpm |
| Speed at rated load | 7500 rpm |
| Torque | 2.5 Nm / 22 in-lbs |
| Spindle thread | M 14 |
| Handle circumference | 193 mm / 7.5594 " |
| Weight (without power cable) | 2.1 kg / 4.6 lbs |
| Cable length | 4 m / 13 ft |
| Vibration | |
| Surface grinding | 6 m/s² |
| Uncertainty of measurement K | 1.5 m/s² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s² |
| Noise emission | |
| | 93 dB(A) |
| Sound pressure level | 55 UD(A) |
| Sound pressure level Sound power level (LwA) | 104 dB(A) |

Scope of delivery

Guard Side handle Inner support flange M-Quick flange nut